

# LinearLED

TYPE:

PROJECT:

QTY:

## SMT-024-192VTD52JWV2, 5in1

5 in 1 output with 0-10v compatibility, with multiple 96w outlets, smart triac dimming 24v, 192w total capacity LED driver with built in junction box



UL US  
LISTED  
E507826

CE

RoHS  
COMPLIANT

### Features

- Flicker free PWM output, constant voltage
- Class 2: 2 x independent 96-watt outputs<sup>1</sup>
- 5-way input: DC0-10v, triac forward or reverse phase, resistor or PWM signal dimmers
- Input voltage range 100-277vac
- Integrated isolated HV and LV junction boxes with multiple knock-outs
- Protection against short circuit, overloading, and over temperature
- Suitable for dry, damp, and wet location
- Built-in PFC function, PF>0.98
- Efficiency>87% / load: 0~100%
- 7-year warranty
- Class 2

<sup>1</sup> Do not exceed 96 watts on any individual output. Wiring runs must be considered when prewiring.

SPECIFICATION SHEET



TYPE:	PROJECT:	QTY:
-------	----------	------

Specifications

Output	DC Voltage	24V
	Voltage Tolerance	±0.5V
	Voltage Regulation	±0.5%
	Voltage Tolerance	±0.5V
	Load Regulation	±1%
	Rated current	2*4A
	Rated power	192W (2*96W)
Input	Voltage Range	100-277VAC
	Frequency Range	47~63HZ
	Power Factor (Typ.) @full load	0.99@120VAC   0.94@277VAC
	THD (Typ.) @full load	<20%
	Inrush Current (Typ.)	15A, 50%, 1.4ms
	Full Load Efficiency (Typ.)	87%@120VAC, 89%@277VAC
	AC Current (Typ.)	2.3A
	Inrush Current (Typ.)	19A (twidh=1.3ms) @120VAC; 38A (twidh=960us) @277VAC
Leakage current	<0.50mA	
Protection	Short Circuit	shut down o/p voltage, re-power on to recover after fault condition is removed
	Over loading	≤120% constant current limiting, auto-recovery
	Over temperature	100°C±10°C shut down o/p voltage, automatically recover after cooling.
	Over Current	≤1.4*I out
Environment	Working TEMP.	-40~+60°C
	Working Humidity	20~90%RH, non-condensing
	Storage TEM. Humidity	-40~+80°C, 10~95%RH
	TEMP. coefficient	±0.03%/°C (0~50°C)
	Vibration	10~500Hz 2G 10min./1 cycle, period for 60min.each along X, Y, Z axes
Safety & EMC	Safety standards	UL8750+UL1310
	Withstand voltage	I/P-O/P: 1.88KVAC
	Isolation resistance	I/P-O/P:100MΩ/500VDC/25°C/70%RH
	EMC EMISSION	FCC Part 15 B
Others	Weight	2.3Kg
	Size	280*125*45mm
Notes	1. All parameters NOT specially mentioned are measured at 110V & 277VAC input, rated load and 25°C of ambient temperature. 2. Tolerance: includes set us tolerance, line regulation and load regulation.	